



RNJet H2+

- No maintenance
- No mess
- High speed
- Hassle free



RNJet H2+

- Operates standalone with 7" touchscreen LCD Controller and network-based with ability to plug up to 100 printers to special RN Windows-based Software over Ethernet
- 2 heads printing up to 25 mm height, or up to 12.7 mm each on different sides, different information, on the same production line, with the same speed
- Maximum drying time for non-porous material is 1 to 3 seconds
- Throw distance up to 8 mm
- Could print in different colors such as black, pigmented white and yellow, blue, red, and more.
- Dynamic database printing
- Downwards or side-printing

Nozzle	Thermal HP Head TIJ 2.5
Drying time	1 to 3 seconds depends on material
Number of Heads	2
Printing Height	Up to 12.7 mm each head
Printing Distance	Up to 8mm
Print Content	Text, Auto Date and Time, Expiry Date, Batch Number, Serial Number, shifts, Logo, QR Code, Barcodes, Databases
Supported database format	.csv
Storage	More than 1000 Messages
Printing Length	Up to 4400 mm
Printing Speed	300 dpi = Up to 90 m/min 150 dpi = Up to 180 m/min
Ink Color	Black, Pigmented white and yellow, blue, red, and more
Ink Type	Variety of solvent-based inks, water-based and food grade ink
External Interface	USB, RS232, Ethernet
Power	12V – 5 A
Operating Conditions	Temperature: 0°C - 45°C Relative Humidity: 20% - 80%
Printing Material	Porous and Non-Porous material including Glass Bottles and Containers, Plastic Bottles and Containers, Rubber Parts, Tins and Cans, Metal Components, Flexible Plastic Films, Shrink Wraps, Woods, PVC Pipes, Epoxy Laminate & PCB Boards, Molded Plastics, Cardboard and Recycle papery, Corrugated Boxes and Wood



MANUFACTURED BY: RN MARK INC
 DISTRIBUTED BY: RNJET INC
 25-16 SIMS CRES.,
 RICHMOND HILL, ON
 L4B 2P1 CANADA
 WWW.RNMARK.COM
 INFO@RNMARK.COM